

KLONDIKE AW Hydraulic Fluids: ISO 22, 32, 46, 68, 100



PRODUCT DESCRIPTION

KLONDIKE Anti-Wear (AW) Hydraulic Fluids are designed for high performance hydraulic systems. These fluids provide excellent operating and maintenance benefits for increased productivity.

APPLICATIONS

KLONDIKE Anti-Wear Hydraulic Fluids are recommended for vane, piston, or gear-type hydraulic pumps in heavy duty and industrial service.

Check your owner's manual for correct fluid viscosity



SPECIFICATIONS AND APPROVALS

KLONDIKE Anti-Wear Hydraulic Fluids are recommended for use where the following specifications are listed:

- **Eaton-Vickers** M-2950-S (Mobile) and I-286-S (Stationary)
- **Parker Hannifin** (Denison) HF2
- **DIN** 51524-2

FEATURES AND BENEFITS

KLONDIKE Anti-Wear Hydraulic Fluids are manufactured with paraffinic base oils and high performance additives. They provide trouble free service in high output hydraulic systems at high temperature and pressure. This hydraulic fluid is designed to operate over a broad temperature range, resulting in lower maintenance cost and production down time. KLONDIKE Anti-Wear Hydraulic Fluids have increased discharge flow rates and decreased internal pump leakage rates resulting in increased hydraulic system pumping efficiency, and therefore fewer fluid changes and less used fluid disposal. These hydraulic oils may also be used in general purpose lubricants where straight mineral oils and conventional rust and oxidation inhibited oils are recommended.

KLONDIKE Anti-Wear Hydraulic Fluids deliver value through the following benefits:

- **Long equipment life** — anti-wear additives minimize wear by protecting surfaces even when heavy loads cause lubricant film breakdown.
- **Minimized downtime** — rust and oxidation inhibitor system helps prevent the production of rust formation as well as deposits, varnish, and sludge, which can damage metal surfaces and oil seals.
- **Smooth operation** — excellent fluid stability and water separation characteristics promote filterability even in the presence of water contamination. Anti-foam and air release properties help ensure smooth operation and high system efficiency.



KLONDIKE AW Hydraulic Fluids

TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	KLONDIKE				
		ISO 22	ISO 32	ISO 46	ISO 68	ISO 100
Oxidation Characteristics (hours)	ASTM D943	2000	2000	2000	2000	2000
Viscosity @ 40°C (cSt)	ASTM D445	22.0	31.9	45.8	68.0	100.0
Viscosity @ 100°C (cSt)	ASTM D445	4.35	5.46	6.9	8.8	11.5
Viscosity Index	ASTM D2270	105	114	106	102	100
Flash Point °C	ASTM D92	210	216	230	249	260
Pour Point °C	ASTM D5950	-40	-37	-34	-30	-27
Zinc, wt%	ASTM D5185	0.03	0.03	0.03	0.03	0.03
Gravity; °API	ASTM D4927	33.0	33.5	30.7	29.9	29.0
Specific Gravity @ 60°F	ASTM D4052	0.85	0.854	0.8578	0.864	0.855

All stated physical properties are typical of standard production and may vary.

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other KLONDIKE product, please visit www.klondikelubricants.com or call 1-877-293-4691. When disposing of used product, be responsible to the environment.

BRAVING THE FORCE OF MOVEMENT

KLONDIKE stands for robust, reliable, high quality products tailored to suit the requirements of the on- and off-road heavy duty, automotive and industrial markets. Our solutions span from trend-setting retail lubricants through small-batch custom formulations to large bulk orders ready for immediate delivery.

The extensive KLONDIKE product range includes premium oils, lubricants, greases, chemicals and specialty fluids formulated with virgin base oils and protective inhibitors. Designed to handle the most extreme climates and operating conditions, the KLONDIKE products protect and extend the life of your equipment, optimize performance and improve productivity while meeting and exceeding industry standards and specifications.

KLONDIKE Lubricants Corporation

Toll-free 1-877-293-4691

info@klondikelubricants.com
www.klondikelubricants.com

