

















# **KLONDIKE®**




**Independent Canadian Corporation** 

360 Oils and Lubricants
15 Million Litres in Stock throughout All 13 Provinces and Territories

Heavy Duty Engine Oils	6
Automotive Engine Oils	12
Gear Lubricants	16
Transmission Fluids	22
Hydraulic Fluids	28
Industrial & Functional Fluids	34
Greases	40
Biodegradable Lubricants	44





# INTRODUCING KLONDIKE EUROPEAN FULL SYNTHETIC ENGINE OILS. MADE IN EUROPE.

Meet the high-performance KLONDIKE European Automotive Engine Oils, designed and made in Europe.

The KLONDIKE European formulated engine oils are high-tech, specialized, and modern full synthetic fluids that provide value through the following benefits:

- Extended engine life reduced friction for excellent protection against engine wear; outstanding engine cleanliness and exhaust system durability.
- **High viscosity index** highly resistant to viscosity shear loss and thermal breakdown from extended high temperature operation for long lubricant life.
- **Superior fuel economy –** high efficiency for superior fuel economy and emission reduction.



Formulated using a careful selection of high-performance synthetic base oils with premium additive chemistry, KLONDIKE's robust technology meets the demanding specifications and approvals of European OEMs, by resisting oxidation, oil thickening, and the formation of sludge inside the engine.

#### **OEM APPROVED BY: \***







Applications include modern European gasoline or diesel engines, with or without turbo-charging; including diesel engines with pump-injector-unit, TDI, or common rail designs. Provides reliable, long-term protection of diesel particulate filters, and other exhaust or emission after-treatment devices.







### can save you space, time and money

KLONDIKE EZE-BOX is a 22 L oil box with an easy-to-pour valve. EZE-BOX bag-in-box oil dispensing system allows for maximum efficiency when used with EZE-RACK and EZE-JUG.

# Effective, stackable and space-saving design

When used with EZE-RACK, you can store and use 8 EZE-BOXES taking only 26" by 30" floor space: boxes are positioned 2 per shelf for a total of 6 boxes ready for dispensing and 2 boxes on the bottom inventory shelf. EZE-BOX can also easily fit on a retail shelf or be stacked for easy transportation, storage and display.

## Lero product contamination

The EZE-BOX valve allows for adjustable and easy oil flow. The flexible internal bladder allows for virtually all oil to dispense without letting any contaminants such as airborne dust and moisture to come in contact with the fluid.

## Efficient and time-saving packaging

EZE-BOX makes an oil change faster and easier when compared to traditional quart bottles, thus saving valuable time for you and your customers. The cardboard box folds down completely for easy and quick recycling.



**DISPENSING JUGS** KL-EZEJUG

RACK KI -F7FRACK KLONDIKE heavy duty engine oils are formulated to assist in maximizing engine life and minimizing wear. Our advanced processes and technologies enable KLONDIKE heavy duty motor oils to strike a balance between durability, emission control, optimized drain intervals, and improved efficiencies for your equipment.

KLONDIKE API CK-4 heavy duty engine oils are a direct successor and replacement for API CJ-4 fluid technology. API CK-4 fluids are fully backwards compatible and supersede CJ-4 and previous service categories. KLONDIKE API CK-4 fluids offer improvements in fuel efficiency, oxidation resistance, viscosity shear stability, and aeration control over the previous fluid technologies. KLONDIKE heavy duty oils have been approved by world's leading manufacturers\*, including:




















= Full Synthetic



SAE 10W-30 CK-4 Synthetic Blend is OEM certified by Cummins, Detroit Diesel, Volvo, Mack,


















Price:













Price:









KL-HD0580



KL-HD0582



KL-HD0590

SAE 15W-40 CK-4 is OEM certified by Cummins, Detroit Diesel, Volvo, Mack, Ford, and Renault; and recommended for use in all engines specifying API CK-4 Service Category and SAE 15W-40.





KL-HD0595





SAE 0W-30 CK-4 Full Synthetic is recommended for use in heavy duty engines specifying API Service Categories CK-4, CJ-4, CI-4 PLUS, CI-4, and SAE grade 0W-30.





KL-HD2060









Price:





SAE 0W-40 CK-4 Full Synthetic is recommended for use in heavy duty engines specifying API Service Categories CK-4, CI-4 PLUS, CI-4, and SAE grade 0W-40.











KL-HD2595

KL-HD2599

Price:















SAE 5W-40 CK-4 Full Synthetic is OEM certified by Detroit Diesel, Volvo, Mack, Ford, and Renault;







Price:

SAE 15W-40 CK-4 Full Synthetic is recommended for use in heavy duty engines specifying API CK-4 Service Category and SAE 15W-40.





KL-HD3560





KL-HD3590



KL-HD3595



KL-HD3599

Price:



SAE 10W CF Heavy Duty Engine Oil is recommended for use in four-stroke gasoline and diesel engines where SAE 10W monograde meeting API CF is specified.













**DRUM** KL-HD6080 KL-HD6090 KL-HD6095

KL-HD6099

Price:







KL-HD6360



engines where SAE 30 monograde meeting API CF-2 is specified.





KL-HD6390 KL-HD6395

SAE 30 CF-2 Heavy Duty Engine Oil is recommended for use in four-stroke gasoline and diesel

KL-HD6399

Price:



SAE 40 CF-2 Heavy Duty Engine Oil is recommended for use in four-stroke gasoline and diesel engines where SAE 40 monograde meeting API CF-2 is specified.



KL-HD6660



KL-HD6680



KL-HD6690



KL-HD6695



Price:

SAE 50 CF-2 Heavy Duty Engine Oil is recommended for use in four-stroke gasoline and diesel engines where SAE 50 monograde meeting API CF-2 is specified.







KL-HD6890



KL-HD6895



KL-HD6880

Price:

SAE 15W-40 Low Ash Natural Gas is recommended for use in heavy duty on-road turbo-charged or naturally aspirated engines running on natural gas and requiring low ash engine oil.







KL-HD7090



KL-HD7095



KL-HD7080

Price:

**SAE 40** 

SAE 40 Low Ash Natural Gas is specifically designed for use in medium and high speed (rpm) engines fueled by pipeline natural gas.









**DRUM** KL-HD7490

KL-HD7495

KL-HD7499

Price:

**SAE 40** 

SAE 40 Low Ash Sour Natural Gas is recommended for heavy duty stationary turbo-charged or

naturally aspirated, stoichiometric or lean burn engines running on landfill or organic/bio gas and requiring low ash engine oil.







DRUM KL-HD7680 KL-HD7690

KL-HD7695

BUI K KL-HD7699

Price:



**SAE 40** 



corrosive materials.





SAE 40 Mid Ash Sour Natural Gas is recommended for use in medium and high speed (rpm) gas engines fueled by processed or pipeline natural gas or other gas sources that may contain

SAE 20W-40 Railroad Engine Oil is an advanced ashless formulation for large diesel engines in railroad, marine, and power generation applications. Designed for use in heavy duty diesel engines

SAE 40 Railroad Engine Oil is an advanced ashless formulation for large diesel engines in

Price:

KL-HD7890 KL-HD7895







specifying SAE 20W-40 multigrade zinc-free engine oil.

KL-HD8290

KL-HD8295


KL-HD8299

Price:













KL-HD8495

KL-HD8499

#### Price:

**AUTOMOTIVE ENGINE OILS** 

GEAR LUBRICANTS

TRANSMISSION FLUIDS

HYDRAULIC FLUIDS

INDUSTRIAL OILS

**GREASES** 

KLONDIKE advanced technology automotive engine oils are formulated for optimum efficiency and are designed for use in modern, highly fuel efficient engines that are subject to increasing levels of stress such as stop-and-go city driving, frequent short trips, extreme high and low operating temperatures, extended idling and towing. KLONDIKE synthetic blend and full synthetic motor oils for passenger cars offer superior oxidation stability, extra protection against heavy load conditions, additional high temperature protection, and better cold weather properties than conventional motor oils. Additionally, KLONDIKE premium quality automotive engine oils are formulated under the newest technology and are certified under the latest ILSAC GF-5 and API SN PLUS specifications. This technology is also good for use in the prior ILSAC GF-4 or API SM specifications.










#### **Automotive Engine Oils**









SAE 10W-40 SN PLUS uses a specialized formula for older, high mileage engines. Recommended for use in passenger cars, light trucks, sport utility vehicles, and other stationary or mobile engines.







Price:







Price:



SAE 5W-20 SN PLUS/GF-5 Synthetic Blend is recommended for use in automobiles and other stationary or mobile engines specifying SAE 5W-20 grade and API SN PLUS/GF-5 Service Category.

SAE 20W-50 SN PLUS uses a specialized formula for older, high mileage engines. Recommended for use in passenger cars, light trucks, sport utility vehicles, and other stationary or mobile engines.





KL-LD1040



KL-LD1060



KL-LD1080



KL-LD1082







KL-LD1090 KL-LD1095

KL-LD1099

Price:



**OUART** KL-LD1240

**5 QUART** 

KL-LD1260





SAE 5W-30 SN PLUS/GF-5 Synthetic Blend is recommended for use in automobiles and other stationary or mobile engines specifying SAE 5W-30 grade and API SN PLUS/GF-5 Service Category.



KL-LD1282

DRUM KL-LD1290 KL-LD1295

KL-LD1299

Price:

#### **Automotive Engine Oils**



Price:

stationary or mobile engines specifying SAE 10W-30 grade and API SN PLUS/GF-5 Service Category. KL-LD1440





KL-LD1480



**EZE-BOX** KL-LD1482



SAE 10W-30 SN PLUS/GF-5 Synthetic Blend is recommended for use in automobiles and other

KL-LD1490



KL-LD1495



KL-LD1499



KL-LD2840

SAE OW-16 SN PLUS Full Synthetic is a highly advanced, 100% synthetic engine oil formulation engineered to provide exceptional resistance and recommended for use in stationary or mobile engine specifying SAE 0W-16 grade and API SN PLUS/GF-5.



Price:



use in stationary or mobile engine specifying SAE 0W-20 grade and API SN PLUS/GF-5. KL-LD3040





KL-LD3060





KL-LD3090



SAE 0W-20 SN PLUS/GF-5 dexos1° Full Synthetic is GM dexos1° certified and recommended for

KL-LD3095



KL-LD3099

Price:



**dexos** 



Price:





**5 QUART** KL-LD3260



specifying SAE 5W-20 grade and API SN PLUS/GF-5.

**EZE-BOX** KL-LD3282



**DRUM** KL-LD3290



KL-LD3295

SAE 5W-30 SN PLUS/GF-5 dexos1° Full Synthetic is GM dexos1° certified and recommended for



KL-LD3299



KL-LD3440

**5 QUART** 

KL-LD3460

KL-LD3482

**EZE-BOX** 

use in stationary or mobile engine specifying SAE 5W-30 grade and API SN PLUS/GF-5.

**DRUM** KL-LD3490



KL-LD3495

KL-LD3499








### **Automotive Engine Oils**



SAE 5W-30 Euro Low SAPS Full Synthetic is recommended for use in European qasoline and diesel fueled engines. Specially formulated to exceed demanding OEM requirements for fuel economy,







KL-LD4660



KL-LD4690



KL-LD4695















SAE 5W-30 Euro Mid SAPS Full Synthetic is an extended service life, premium engine oil with specialty base oils and additives. Designed for use in European gasoline and diesel fueled engines.



KL-LD4840



KL-LD4860













Price:



SAE 5W-40 SN/CF Euro Full Synthetic is recommended for use in modern European 4, 6 and 8+ cylinder multi-cam, multi-valve, naturally aspirated, super- and turbo-charged engines.



**EZE-BOX** 

KL-LD5082

Price:

**EURO** 



SAE 5W-40 Euro Mid SAPS Full Synthetic is a very high-performance engine oil that resists oxidation, sludge deposits, and viscosity loss. Designed for use in European gasoline and diesel fueled engines.



KL-LD5240





KL-LD5260



KL-LD5290



KL-LD5295











IVII	υ	5F	NP.
Р	ri		۔



Tough operating conditions are no match for KLONDIKE **gear** oils. They are specially formulated for maximum protection, durability, and efficiency no matter what climate or conditions are prevalent. Only the finest technology available is used in manufacturing our premium synthetic gear lubricants. KLONDIKE robust formulations are designed for gears and differentials that place rigorous demands on fluid technology and require extreme temperature and pressure protection. Driveline components in today's automotive and heavy duty vehicles have become increasingly stressed by increased engine output, higher operating temperatures, and extended service intervals. KLONDIKE's advanced gear oil technology protects against severe wear while balancing fluid durability in heavy load conditions, including extended drain intervals when applicable.

= Conventional



= Synthetic Blend



= Full Synthetic

**Gear Lubricants** 





SAE 80W-90 GL-5 is designed for differentials, manual transmissions, power take off units, and final drives specifying SAE 80W-90 and API GL-5/MT-1.















Price:

SAE 85W-140 GL-5 is designed for differentials, manual transmissions, power take off units, and final drives specifying SAE 85W-140 and API GL-5/MT-1.







KL-GL1390



KL-GL1395



Price:

SAE 75W-90 GL-5 Full Synthetic is recommended for use in heavy duty gear applications specifying SAE 75W-90 and API GL-5/MT-1 including limited slip.



KL-GL2040 Price:







KL-GL2080



KL-GL2085



KL-GL2090





KL-GL2099

KL-GL2095

SAE 75W-140 GL-5 Full Synthetic is recommended for use in heavy duty gear applications specifying SAE 75W-140 and API GL-5/MT-1 including limited slip.















KL-GL2485 KL-GL2490

KL-GL2495

KL-GL2499

Price:

#### **Gear Lubricants**









KL-GL3690

drives of all sizes where ISO 100 is specified.

drives of all sizes where ISO 68 is specified.

KL-GL3699 KL-GL3695

Price:



KL-GL3680







KL-GL3899

Price:

ISO 150 EP is designed for heavily loaded plain bearings, enclosed gear drives, and reducers on drives of all sizes where ISO 150 is specified.

ISO 68 EP is designed for heavily loaded plain bearings, enclosed gear drives, and reducers on

ISO 100 EP is designed for heavily loaded plain bearings, enclosed gear drives, and reducers on









KL-GL4090



KL-GL4095 KL-GL4099

Price:

ISO 220 EP is designed for heavily loaded plain bearings, enclosed gear drives, and reducers on drives of all sizes where ISO 220 is specified.











KL-GL4280

KL-GL4290

KL-GL4295

KL-GL4299

Price:

ISO 320 EP is designed for heavily loaded plain bearings, enclosed gear drives, and reducers on drives of all sizes where ISO 320 is specified.









PAIL KL-GL4490 KL-GL4480

KL-GL4495 KL-GL4499

Price:

**Gear Lubricants** 









KL-GL4690





ISO 460 EP is designed for heavily loaded plain bearings, enclosed gear drives, and reducers on

ISO 150 EP Full Synthetic is formulated for industrial bearings and gear applications operating in

ISO 220 EP Full Synthetic is formulated for industrial bearings and gear applications operating in

ISO 320 EP Full Synthetic is formulated for industrial bearings and gear applications operating in

ISO 460 EP Full Synthetic is formulated for industrial bearings and gear applications operating in

KL-GL4695

Price:

very heavy duty and shock-loaded conditions where ISO 150 is specified. PAIL









KL-GL6080

KL-GL6090

KL-GL6095

KL-GL6099

very heavy duty and shock-loaded conditions where ISO 220 is specified.

Price:









KL-GL6280

KL-GL6290

KL-GL6295 KL-GL6299

Price:





KL-GL6480



KL-GL6490



KL-GL6495



very heavy duty and shock-loaded conditions where ISO 320 is specified.

KL-GL6499

Price:

Price:



very heavy duty and shock-loaded conditions where ISO 460 is specified.







KL-GL6680 KL-GL6690

KL-GL6695 KL-GL6699

### **Gear Lubricants**















KL-GL6899

ISO 680 EP Full Synthetic is formulated for industrial bearings and gear applications operating in

KL-GL6880 KL-GL6890 KL-GL6895 KLONDIKE transmission fluids are formulated for use in a full range of automatic transmissions and provide premium shifting characteristics. This extensive line of automatic transmission fluids offers smooth yet responsive shifting, long service life, and outstanding fuel efficiency. KLONDIKE transmission oils are engineered to provide improved performance, extended transmission life, as well as premium flow characteristics at very low temperatures and protection against oxidation, varnish and sludge at high temperatures.

= Conventional



= Synthetic Blend



= Full Synthetic

**Transmission Fluids** 



Price:



ATF MD3 is designed and recommended for use in most pre-2006 automatic transmissions that reference specifications GM DEXRON III, Ford MERCON and similar.

















KL-TF1080 KL-TF1060

KL-TF1090

DEXRON®-VI / MERCON® LV ATF Full Synthetic is OEM certified by General Motors and Ford.

KL-TF1095

Price:









Approvals:



**MERCON® LV** 



Heavy Duty ATF Full Synthetic is formulated for high performance and long service life in heavy duty automatic transmissions in urban and rural commercial vehicles. KL-TF3160







KL-TF3180



KL-TF3190



KL-TF3195



KL-TF3199

Price:

**CVT Fluid Full Synthetic** is formulated for belt and chain driven continuously variable transmissions. Do not use as a replacement for ATF.









Price:

23

#### **Transmission Fluids**



ATF Universal Full Synthetic is one highly advanced and truly universal automatic transmission fluid ideal for global application. Meets the performance requirements of (but not limited to):

- ATF Type A-Suffix A
- Aisin Warner AW-1, JWS 3309, 3314, 3317, 3324, SCS, M315 A-1, T-IV
- Acura ATF-Z1 (VTM-4)
- Allison C-3, C-4, TES-389
- American Motors ATF+3(MS7176-E), ATF+4(MS9602)
- Audi ZF 5HP (18FL, 19FL, 24A, 30), 6HP (1375.4), TL52162 (LT71141), G-052-025-A2, G-052-162-A1/A2, G-052-182-A2, G-052-990-A2
- BMW ZF 5HP (18FL, 19FL, 24A, 30), 6HP (1375.4), LA2634, ETL-7045E, ETL-8072B, N402, LT71141 83.22.9.400 (272, 275), 83.22.9.407 (738, 765, 807, 858, 859), 83.22.0.397 (114), 83.22.0.403 (248, 249)
- Caterpillar Power Shift TO-2
- Chrysler AS68RC "T-IV", AS69RC, ATF+3 (MS7176-E), ATF+4 (MS9602), ZF 8HP, ZF 9HP
- Daewoo LT 71141
- Fiat "all vehicles", Type T-IV
- Ford Mercon<sup>e</sup>
  - > Mercon (XT-2-QDR,XT-2-QSM syn)
  - > Mercon V (XT-5-QM, XT-5-DM, WSS-M2C-202B)
  - > Mercon SP (XT-6-QSP, XT-6-DSP, WSS-M2C-919D except 6HP26 / 6R60 / 6R75 transmissions
  - > Mercon LV (XT-10-QLV, WSS-M2C-938A)
  - > WSS-M2C33-A/B/C/D/F/G, WSS-M2C138-CJ, WSSM2C166-H, 185-A, 195-A, 202-B, WSS-M2C 922-A1, 924-A (XT-8-QAW)
- GM Dexron<sup>®</sup>
  - > Dexron VI, III-H, III-G, II-E, II

  - > GM Transfer Fluid 12378515 (Transynd® applications)
  - > GM Transfer Case 12378396, 12378508 (Auto Trak II)
- Honda ATF-Z1, VTM-4, DW-1, DPF
- Hyundai SP-II, SP-III, SP-IV, SP-4M, WS-9638
- Infiniti Matic-D, Matic-J, Matic-K, Matic-S
- IDEMITSU K17, JATCO 3100 PL085
- Isuzu Besco ATF-II, ATF-III
- Jaquar ZF 5HP24, ZF 6HP26, LT71141, JLM20238, JLM21044, ATF 3403 M115, M1375.4
- JASO M315-2004 1A, 2A
- Jeep ATF+3, ATF+4, AS68RC (T-IV)
- Kia SP-II, SP-III, SP-IV, SP-4M, ATF Red 1
- Lexus Type T, T-II, T-III, T-IV, WS (JWS 3324)
- MAN 339 A,F, V1, V2, Z1, Z2, Z3
- Mazda ATF-M III, ATF M-3, ATF-MV, V (XT-9-QMM5, FNR 5), FZ
- MERCEDES ZF 4HP20, 223.2, 236.1, 236.10, 236.11, 236.12(NAG 1/2), 236.14, 236.41, 236.5(C-4), 236.6, 236.7, 236.8, 236.9, 722.3, 722.4, 722.5, 722.6, 722.9
- Mini Cooper T-IV, 83 22 0 402 413, 83 22 7 542 290

- Mitsubishi Diamond SP-II, SP III, SP IV, Dia Queen J2, J3
- Nissan Matic-D, Matic-J, Matic-K, Matic-S, 402
- Porsche ZF 5HP19FL, ZF 5HP20, LT71141, ATF 3403-M115, T-VI, JWS 3309
- Renault "all vehicles"
- RENK DOROMAT
- SAAB JWS 3309, 93 165 146/147
- SATURN T-IV, GM TASA, T-IV ATF, GM WS ATF
- Shell 3403, 3353, LA2634, ATF-134, M-1375.4, M-1375.5, M-1375.6. M-12108
- Subaru ATF, AT-HP
- Suzuki ATF 2326, 2384K, JWS 3309, 3314
- Texaco ETL-7045E, ETL-8072B, N402
- Toyota Type T, T-II, T-III, T-IV, Type D-2, WS (JWS 3324), Toyota Prius (WS)
- VICKERS M-2950-S, I-286-S
- VOITH G607 (55.6335.XX), G1363 (55.66336.XX), TURBO, ZF, ECOMAT, ZF TE-ML 02F, 03D, 04D, 05L, 09, 11B, 14A/B/C, 16L, 17C
- Volvo 97340, 97341, 97342 (AT-102), 1161640, 1161540, 1161521, T-IV
- Volkswagen ZF 5HP (18FL, 19FL, 24A, 30), 6HP (1375.4), TL 52162 (LT71141), TL 52533, G-055-025-A2, G-052 162-A1/A2, G-052-182-A2, G-052-990-A2, G-052-025-A2, G-055-540-A2
- ZF 8HP, 9HP





KL-TF3080



KL-TF3082



KL-TF3090





KL-TF3095

KL-TF3099



#### **Transmission Fluids**



Price:





KL-TF4080



KL-TF4085



KL-TF4090



SAE 30 TDTO-4 Transmission and Drivetrain Fluid is designed for heavy duty mobile and stationary

SAE 50 TDTO-4 Transmission and Drivetrain Fluid is designed for heavy duty mobile and stationary

KL-TF4095



KL-TF4099



Price:

SAE 10W TDTO-4 Transmission and Drivetrain Fluid is designed for heavy duty mobile and stationary equipment where Caterpillar TO-4 or Allison C-4 fluids for SAE 10W grade are specified. KL-TF6080









KL-TF6090 KL-TF6095



Price:









equipment where Caterpillar TO-4 or Allison C-4 fluids for SAE 50 grade are specified.



KL-TF6480







**KL-TF6495** KL-TF6490

KL-TF6499

Price:

All Season Synthetic Blend TDTO-4 is for all season use across a wide T° range in heavy duty mobile and stationary equipment where Caterpillar TO-4, TO-4M, or Allison C-4 fluids are specified.







KL-TF7080







Price:

### **Transmission Fluids**















KL-TF7495

KLONDIKE anti-wear hydraulic fluids are designed to operate in the most extreme conditions. Today, operating conditions require greater precision and pressure than ever before. While advanced systems do more work and are more responsive, they are also more vulnerable to wear and deposit formation when operated at higher temperatures and pressures. Highly tested KLONDIKE hydraulic lubricants are specially formulated with the finest base oils and additive systems that deliver unrivaled performance and protection.

= Conventional



= Synthetic Blend



= Full Synthetic

**Hydraulic Fluids** 











KL-HF1095

duty and industrial service where ISO 22 viscosity is specified.



Price:

Red AW 22 Hydraulic Fluid is recommended for vane, piston, or gear-type hydraulic pumps in heavy duty and industrial service specifying ISO 22 viscosity. Dyed in red for better visibility.

AW 22 Hydraulic Fluid is recommended for vane, piston, or gear-type hydraulic pumps in heavy











KL-HF1195

Price:

AW 32 Hydraulic Fluid is recommended for vane, piston, or gear-type hydraulic pumps in heavy duty and industrial service where ISO 32 viscosity is specified.





KL-HF1260









KL-HF1295

KL-HF1299

Price:

Red AW 32 Hydraulic Fluid is recommended for vane, piston, or gear-type hydraulic pumps in heavy duty and industrial service specifying ISO 32 viscosity. Dyed in red for better visibility.









KL-HF1280



KL-HF1290

KL-HF1395 KL-HF1399



AW 46 Hydraulic Fluid is recommended for vane, piston, or gear-type hydraulic pumps in heavy









KL-HF1499

Price:

AW 68 Hydraulic Fluid is recommended for vane, piston, or gear-type hydraulic pumps in heavy duty and industrial service where ISO 68 viscosity is specified.

AW 100 Hydraulic Fluid is recommended for vane, piston, or gear-type hydraulic pumps in heavy

Multi-Viscosity AW 15 with Arctic Performance Technology is formulated for high performance hydraulic systems in mobile and stationary equipment operating in ultra-low temperatures.

Multi-Viscosity AW 22 with Arctic Performance Technology is formulated for high performance

hydraulic systems in mobile and stationary equipment across a broad temperature range.











KL-HF1680 KL-HF1690

KL-HF1695

KL-HF1699

Price:





KL-HF1899

duty and industrial service where ISO 100 viscosity is specified.

KL-HF1880

KL-HF1890

Price:







**DRUM** KL-HF4880

KL-HF4890

KL-HF4895

KL-HF4899







KL-HF5090



KL-HF5095

KL-HF5099

Price:











Multi-Viscosity AW 36 with Arctic Performance Technology is formulated for high performance

Multi-Viscosity AW 46 with Arctic Performance Technology is formulated for high performance

Long Life Turbine Oil ISO 32 is designed for use in non-geared steam, hydro-electric and gas

Long Life Turbine Oil ISO 46 is designed for use in non-geared steam, hydro-electric and gas

Long Life Turbine Oil ISO 68 is designed for use in non-geared steam, hydro-electric and gas

hydraulic systems in mobile and stationary equipment across a broad temperature range.

hydraulic systems in mobile and stationary equipment across a broad temperature range.

KL-HF5280

KL-HF5290

KL-HF5295

KL-HF5299

Price:









KL-HF5480

KL-HF5490

KL-HF5495

KL-HF5499

Price:









KL-HF6680

DRUM KL-HF6690

KL-HF6695 KL-HF6699

turbines as well as a high temperature bearing lubricant and coolant.

Price:











KL-HF6880

KL-HF6890

KL-HF6895

KL-HF6899

turbines as well as a high temperature bearing lubricant and coolant.

Price:









KL-HF7080

KL-HF7090

KL-HF7095

KL-HF7099

Price:





KL-HF7480 KL-HF7490





KL-HF7495



KL-HF7499

Price:



**5 QUART** KL-HF8060



PAII KL-HF8080



DRUM KL-HF8090



KL-HF8095



Universal Tractor Fluid is the one single fluid that may be used to lubricate all conventional points


on an agricultural or industrial tractor or piece of mobile equipment with a common sump.

Long Life Turbine Oil ISO 150 is designed for use in non-geared steam, hydro-electric and gas

KL-HF8099

Price:
















KL-HF8199

Universal Tractor Fluid Full Synthetic is formulated with Arctic Performance Technology for use

Universal Red Tractor Fluid is a specialized, advanced formulation designed to fulfill the torque



Price:





**PAIL** KL-HF8280

KL-HF8290

Price:



transfer, hydraulic, and power transmission requirements of modern agricultural and other mobile off-road equipment. **PAIL** KL-HF8480



**DRUM** KL-HF8490



**BULK** 

KL-HF8495

KL-HF8499

Price:



WET BRAKE

**Wet Brake Lubricant Full Synthetic** is a specialized heavy duty fluid designed to fulfil VOLVO wet brake WB101 and WB102.





KL-HF8680

DRUM KL-HF8690

ப	~	_	$\overline{}$
_			_
		_	•

The KLONDIKE family of industrial and functional fluids is formulated for exceptional performance and reliability using world-class technologies that have been trusted and proven by industry professionals for many years and is relied on by industry users all year round. Our bar and chain oil is of the highest quality and operates in extreme climatic - high or low temperature - conditions. It offers unsurpassed durability and performance for equipment operating in high heat conditions, and performs flawlessly in the logging and saw mill industries that require the most robust and durable lubricant formulations in order to maximize efficiency and productivity.

= Conventional





= Full Synthetic

**Industrial Oils** 



Bar & Chain Oil is designed for the lubrication of chains, bars, and sprockets of chain saws.



KL-100650

Price:

Light Hi-Tack Bar & Chain Oil is a low viscosity formula for winter use in all types of chain saws with manual or automatic oilers for lubrication of the bar, chain, and sprocket.

Hi-Tack Bar & Chain Oil is a medium viscosity formula for all-season use in all types of chain saws













**DRUM** KL-I01090

KL-IO1095



Price:









PAIL KL-I01260 KL-I01280

**DRUM** KL-I01290

KL-I01295



Price:

KL-I01460

Hi-Tack Bar & Chain Oil is formulated for all season use in chain saws, open bearings, gears, and chains found in industrial applications or anywhere a tacky oil is required.



KL-I01480





DRUM KL-IO1490

KL-IO1495

# **Industrial Oils**





KL-102295

KL-102299

Price:

# ISO 68





KL-I02690





KL-102699

KL-102680

Price:

Rock Drill Oil ISO 100 is formulated for the internal mechanisms and moving parts of pneumatic drilling equipment operating in heavy duty service environments where ISO 100 is specified.

Rock Drill Oil ISO 32 is formulated for the internal mechanisms and moving parts of pneumatic drilling equipment operating in heavy duty service environments where ISO 32 is specified.









KL-102880 KL-I02890

KL-I02895

KL-I02899

Price:

Price:

Rock Drill Oil ISO 150 is formulated for the internal mechanisms and moving parts of pneumatic drilling equipment operating in heavy duty service environments where ISO 150 is specified.







PAIL DRUM KL-I03080 KL-I03090

KL-103095

KL-103099

Rock Drill Oil ISO 220 is formulated for the internal mechanisms and moving parts of pneumatic



Price:

**PAIL** 

KL-103280

drilling equipment operating in heavy duty service environments where ISO 220 is specified. **DRUM** 

KL-I03290





KL-I03295

KL-103299

36

# **Industrial Oils**



duty pipeline compressors pumping hydrocarbons such as natural gas.

DRUM

KL-104490 KL-I04495

Price:







KL-105880









applications where non-detergent oil is specified.

**BULK** KL-105899

demand VRO oil delivery system applications requiring oils meeting API TC.

machine tools such as lathes, planers, shapers, and tapping machines.

ISO 260 Natural Gas Compressor Oil is specifically designed for the lubrication of large, heavy

SAE 30 Non-Detergent Oil is recommended for use in air compressors and other industrial

2-Cycle TC-W3 is a NMMA certified ashless engine oil formulated for use in pre-mix and mix-on-

ISO 68 Way Oil is specifically formulated for use in the lubrication of bearings, slides, and ways of

Price:











KL-106090

Price:







PAIL

KL-107280

**DRUM** 

KL-107290

Price:















KL-107880 KL-107895 KL-107890

KL-107899

# **Industrial Oils**



**ISO 100** 

Tacky Saw Guide Oil ISO 100 is recommended for all types of thin kerf saw blades on modern gang saws and edgers.



Price:

ISO 150

Tacky Saw Guide Oil ISO 150 is recommended for all types of thin kerf saw blades on modern gang saws and edgers.


Dust Suppressant/Form Oil is colorless, odorless, neutral oil for dust suppression and concrete



KL-I08590

Price:











KL-109790

KL-109799



form release as well as other similar commercial applications.





KL-I09990 Price:

KL-109995

KL-109999

38



KLONDIKE produces a range of unique robust and tacky **greases** that provide premium lubrication in difficult operating conditions and are tailored to industry requirements for improved productivity. They are specially engineered for environments with extreme temperature requirement, moisture and dirt contamination, heavy loads, extended maintenance intervals and other conditions that impact performance. Our greases are created with the finest base oils and additives in order to provide outstanding tackiness, lubrication and protection. These formulations will guard against oxidation and wear in extreme pressure and high temperature applications.

**Greases** 

= Conventional



= Synthetic Blend



= Full Synthetic









nKL-GR1630

nKL-GR1680 nKL-GR1685











elements, antifriction bearings, bushings and pins.



Price:

Ultra Tac EP-00 Synthetic Blend is recommended for pressurized auto grease systems, industrial bearings operating at high speed, and where ultra-low To limits the mobility of heavier grease.

Multipurpose Red Grease is recommended for greasing applications of plain bearings, rolling

KLONDIKE nano Full Synthetic EP-1.5 Grease is formulated for use in the most technical and demanding industrial, automotive, and heavy duty equipment applications. Supports a 45%









KL-GR0880

KL-GR0885

KL-GR0890

Price:



Syn Tac EP-00 Synthetic Grease is an extreme pressure, multi-purpose, semi-fluid lithium complex formulation fortified with PAO synthetic base oil, polymers, anti-wear agents, tackiness additives, and rust and oxidation inhibitors.



Price:

## Greases













Price:



Ultra Tac EP-1 Synthetic Blend is designed for heavy duty use in industrial, on- and off-road vehicle, and heavy equipment applications operating in extreme cold T° where NLGI 1 is specified. NLGI GC-LB certified.

Syn Tac EP-1 Synthetic Grease is an extreme pressure, multi-purpose, semi-fluid lithium complex

Ultra Tac EP-0 Synthetic Blend is designed for heavy duty use in industrial, on- and off-road vehicle, and heavy equipment applications operating in extreme cold To where NLGI 0 is specified.





KL-GR1430





KL-GR1490

NLGI GC-LB


NATIONAL LUBRICANT GREASE INSTITUTE NLG

GC-LB

Price:



formulation fortified with PAO synthetic base oil, polymers, anti-wear agents, tackiness additives,



KEG KL-GR1585

Price:



Ultra Tac EP-2 is designed for extreme duty use in a wide variety of industrial, on- and off-road vehicle, and heavy equipment applications where NLGI 2 is specified. NLGI GC-LB certified.







KL-GR1830



KL-GR1880



KL-GR1885



KL-GR1890

Price:



Moly Tac Arctic HD Synthetic Blend Grease is designed for high lubricating performance in extremely cold environments.





KL-GR2285

Price:



**MOLY** 



KL-GR2430



Price:

Moly Tac EP-2 is formulated with 3% molybdenum disulfide for use in heavy duty, shock loaded bearings and bushings in industrial or off-highway equipment where NLGI 2 is required. NLGI GC-LB certified.

Moly Tac EP-1 is formulated with 3% molybdenum disulfide for use in heavy duty, shock loaded

bearings and bushings in industrial or off-highway equipment where NLGI 1 is required.







KL-GR2880





NATIONAL LUBRICANT GREASE INSTITUTE NLGI GC-LB

**Greases** 

Price:

MOLY **BENTONE** 

Moly Tac Bentone High Temp EP-2 Grease is formulated from a special blend of highly refined, high viscosity base oil thickened with bentonite clay.

Open Gear Grease is engineered to protect extremely heavy loaded, slow moving, large open gear

Open Gear Lubricant is specially formulated to protect heavily loaded, slow moving, large open



KL-GR2830

Price:

**GREASE** 



sets operating in severely challenging environments.

KL-GR9080

KL-GR9085

Price:



gear sets when used with spray type application system.



KL-GR9280

KL-GR9285

Price:



The KLONDIKE family of biodegradable lubricants are designed as an environmentally safer alternative to traditional industrial lubricants. With the rise in natural resource based industries being encouraged to monitor the impact and sustainability of the work completed in environmentally sensitive areas, the need for more environmentally safe and efficient products has increased. Our line of biodegradable lubricants are formulated using non-toxic chemistry with no heavy metals to contaminate water or soil, which will greatly reduce the immediate and longterm impact of the fluids on the environment in the event of an oil leak or spill. The KLONDIKE line of biodegradable lubricants are highly stable for smooth operational efficiency, and highly resistant to oxidation and deposit formation for long service life, while providing a high level of environmental conservation and protection.

= Conventional



= Synthetic Blend



**Biodegradable Lubricants** 

= Full Synthetic







Price:

ENVIRO AW 32 Inherently Biodegradable Hydraulic Fluid is an inherently biodegradable,

non-toxic, environmentally friendly fluid. This fluid is recommended for vane, piston, or gear-type hydraulic pumps in heavy duty and industrial service where ISO 32 viscosity is specified.

ENVIRO AW 46 Inherently Biodegradable Hydraulic Fluid is an inherently biodegradable, non-toxic, environmentally friendly fluid. This fluid is recommended for vane, piston, or gear-type

ENVIRO AW 68 Inherently Biodegradable Hydraulic Fluid is an inherently biodegradable, non-toxic, environmentally friendly fluid. This fluid is recommended for vane, piston, or gear-type

hydraulic pumps in heavy duty and industrial service where ISO 46 viscosity is specified.

ENVIRO AW 22 Inherently Biodegradable Hydraulic Fluid is an inherently biodegradable, non-toxic, environmentally friendly fluid. This fluid is recommended for vane, piston, or gear-type





KL-BL0180



KL-BL0190



PAIL

KL-BL0280

Price:

KL-BL0290 KL-BL0295









Price:

PAIL KL-BL0380

DRUM KL-BL0390 KL-BL0395







KL-BL0480

DRUM KL-BL0490

KL-BL0495

Price:

# **Biodegradable Lubricants**





specified.





KL-BL1880

KL-BL1890

KL-BL1895

BIO AW 46 Readily Biodegradable Hydraulic Fluid is a non-toxic, ashless fluid designed for high performance hydraulic systems in mobile and stationary equipment where ISO 46 viscosity is specified.

BIO AW 32 Readily Biodegradable Hydraulic Fluid is a non-toxic, ashless fluid designed for high performance hydraulic systems in mobile and stationary equipment where ISO 32 viscosity is










KL-BL1980

KL-BL1990

KL-BL1995

Price:









PAIL KL-BL2780

KL-B2790

KL-BL2795

Price:

BIO Rock Drill Oil ISO 100 is a readily biodegradable, extreme pressure lubricant designed for the performance and protection of heavy duty pneumatic tools such as rock drills, breakers, jackhammers, and drifters as well as other surface and down-hole equipment.

BIO Rock Drill Oil ISO 150 is a readily biodegradable, extreme pressure lubricant designed for







KL-BL4380

KL-BL4390

KL-BL4395

Price:



the performance and protection of heavy duty pneumatic tools such as rock drills, breakers, jackhammers, and drifters as well as other surface and down-hole equipment.




KL-BL4480

DRUM KL-BL4490

KL-BL4495

Price:






KLONDIKE Brake Blast is an advanced formulation of highly technical solvents that once applied will quickly dissolve and remove grease, oil, brake fluid, road grime, and dirt. This non-chlorinated, low odor formula dries fast, leaves no residue, and is safe for use on most materials including plastics.

KLONDIKE Cleaner/Degreaser is a truly versatile and certified biodegradable all-in-one degreaser. Simply alter the dilutions and it becomes a muscled water based engine degreaser, white wall tire cleaner, vinyl top cleaner, leather, plastic and vinyl cleaner, and a concrete floor degreaser. Effectively removes oil, grease, fat, rust stains, carbon, and dirt.

**Chemicals** 









KL-CH6550

KL-CH6580

KL-CH6590

Price:









KL-CH8680 KL-CH8630

KL-CH8690

Price:

Brake Blast is a non-chlorinated solvent designed to remove contaminants from brake parts

quickly and easily. Surfaces dry residue free for improved, smooth brake performance.

## Warranty

## **KLONDIKE Lubricants Corporation Warranty**

KLONDIKE Lubricants Corporation warrants that at the time of sale, all lubricant, grease, and engine coolant products bearing the KLONDIKE brand meet their written product specifications and are free of defective materials, design, and workmanship.

The KLONDIKE warranty is in addition to, and does not invalidate, any warranty supplied by an original equipment manufacturer when used in accordance with the KLONDIKE written product recommendations and the original equipment manufacturers' written specifications\*\*.

KLONDIKE is 100% committed to our customers. To support this commitment, KLONDIKE Lubricants Corporation will repair or replace equipment parts that have been damaged as a direct result of the failure of any of our products\*.

\*\*For specific warranty details and procedures, contact KLONDIKE Lubricants Corporation at info@klondikelubricants.com.

<sup>\*</sup> TRADEMARKS DISCLAIMER: All OEM product names and trademarks are the property of their respective owners, which are in no way associated or affiliated with KLONDIKE Lubricants Corporation.

# **Comparison Chart**

# **KLONDIKE Cross-Reference Table**

<b>KLONDIKE®</b>	Shell	Chevron	Petro Canada	Esso/Mobil	Conoco-Phillips	Castrol
AW Hydraulic Fluid	TELLUS S2	HYDRAULIC OIL AW	N/A	NUTO H SERIES	HYDRAULIC AW	HYSPIN AWS
MAX Long Life Hydraulic Fluid	TELLUS S2 MX	RANDO HD	HYDREX AW	DTE 20 SERIES	MEGAFLOW AW	PARADENE AW
Multi-Viscosity Hydraulic Fluid	TELLUS S2 V	RANDO HDX	HYDREX MV, MV ARCTIC	UNIVIS HVI, UNIVIS N	POWERFLOW HE HVI	DUAL RANGE HV
15W-40 CK-4 Engine Oil	ROTELLA T4 TRIPLE PROTECTION	DELO 400 SDE	DURON HP, DURON SHP	DELVAC 1300 SUPER, DELVAC ELITE	FLEET SUPREME EC, GUARDOL ECT	CRB MULTI, VECTON
0W-30/0W-40/5W-40 CK-4 Full Synthetic Oil	ROTELLA T6	DELO 400 SYNTHETIC LE (SAE 5W-40 only)	DURON UHP SERIES	DELVAC 1 ESP, DELVAC ELITE 222	TRITON ARTIC	ELIXION (SAE 5W-30 only)
80W-90 GL-5 Gear Oil	SPIRAX S4 AX	DELO GEAR EP-5, DELO GEAR ESI	TRAXON	MOBILUBE HD PLUS	MP GEAR LUBE	AP GEAR
75W-90/75W-140 Full Synthetic Gear Oils	SPIRAX S6 AXME, AXRME	DELO SYN- GEAR HD, XDM	TRAXON-E SYNTHETIC	DELVAC 1 GEAR OIL	MP GEAR LUBE FULL SYNTHETIC	SYNGEAR
Universal Tractor Fluid	SPIRAX S4 TXM	TRACTOR FLUID 1000 THF	DURATRAN	MOBIL HYDRAUL	POWERTRAN	TRACTOR HYDRAULIC
EP-0, EP-1 & EP-2 Grease	GADUS S2 V220, GADUS S3 V220C	ULTRA DUTY EP, ULTI-PLEX EP	PRECISION/ VULTREX	DELVAC XTREME, EPIC 102, MOBILUX, RONEX, UNIREX	MEGA PLEX XD3, RED TAC, TACNA HD	MP GREASE, PYROPLEX GOLD, PYROPLEX RED
Bar & Chain Oil ISO 90/150/220	CHAIN OIL	RED CHAIN BAR OIL	DURATAC	MOBIL HD CHAIN OIL	SPECIAL BAR & CHAIN	N/A
Zinc Free Hydraulic Fluid	TELLUS S3 M	CLARITY	ENVIRON AW	DTE 10 EXCEL	ECOTERRA	N/A

# **Industry Applications**



#### **AGRICULTURE**

KLONDIKE agriculture fluids are formulated to ensure maximum productivity in a critically time sensitive seasonal industry. Proper lubrication goes beyond protection, and our lubricants are created with premium base oils and inhibitors to disperse soot and reduce sludge. The KLONDIKE engine oils provide durability and reliability, and consistent performance during the long, demanding hours of the harvest season.



#### **AUTOMOTIVE**

The KLONDIKE product lines of automotive engine oils and automatic transmission fluids employ advanced formulations to meet and exceed the world's leading automakers requirements. Our cutting-edge synthetic blend and full synthetic formulas are engineered to provide maximum protection and optimum performance in all driving conditions. Certified by GM's dexos1°, GM's DEXRON°-VI, Ford's MERCON° LV.



#### **CONSTRUCTION & EXPLORATION**

Understanding the rigorous challenges and the nohassle requirements placed on construction and exploration equipment, KLONDIKE has engineered robust lubricants for environments with moisture and dirt contamination, heavy loads, extended maintenance intervals and other harsh conditions. The KLONDIKE Arctic Performance Technology line ensures maximum protection with smooth and reliable performance in extreme cold weather conditions.



#### **FORESTRY**

With relentless work schedules, environmental challenges, competitive pricing and harsh climatic conditions faced by the forestry industry, we are continually enhancing the KLONDIKE range of oils and lubricants to ensure harvesting, transportation and wood-production is as efficient and cost effective as possible. Our line of tough greases is blended for maximum lubrication and adhesion with minimum flyoff, making them ideal for milling operations.

# **Industry Applications**



#### **INDUSTRIAL**

KLONDIKE has a vast range of premium industrial lubricants from conventional hydraulic fluids through to premium environmentally friendly oils. We provide solutions that increase uptime, productivity, and efficiency. The KLONDIKE lubricants can be utilized to extend maintenance intervals and prolong the life of your equipment. Our technical professionals will identify your needs and provide solutions for faster production and greater cost efficiency.



#### **MARINE**

The KLONDIKE range of high quality marine oils is tailored for reliability, stringent safety standards and strict environmental requirements as specified by marine authorities. Engineered for durability and maximum protection, whether it is salt or fresh water, these hardworking lubricants will ensure that your marine vessels or pleasure craft run smoothly and efficiently. Certified by the National Marine Manufacturers Association - NMMA®.



#### **MINING**

We offer a complete selection of oils and lubricants tailored to the requirements of all types of mining operations from equipment to process lubrication. The KLONDIKE line of heavy duty engine oils will deliver optimum efficiency and performance to every application and specification found in the wide range of machinery used in mining. From surface to underground mining our oils and greases are formulated to deliver outstanding equipment protection.



#### **ON-ROAD HEAVY DUTY**

Our heavy duty engine oils are formulated to protect your investment in your equipment and maximize the life of your engine. KLONDIKE heavy duty engine oils provide high performance in extreme temperatures, heavy-load requirements and challenging terrain. They are designed to meet the difficult challenge of effectively balancing durability, extended drain intervals, and emission control. Certified by Cummins, Detroit Diesel, Volvo, Mack, Ford and Renault.

# **KLONDIKE Distribution Facilities**

Dedicated to meeting the delivery needs of our customers, we have warehousing and distribution centres that are strategically located throughout Canada to cater to the time-sensitive nature of your industry.

## **BRITISH COLUMBIA**

## Serving BC

101-1005 Derwent Way 3078-275th Street
Delta, BC V3M 5R4 Langley, BC V4W 3L4

## **ALBERTA**

Serving Northern BC, AB, SK, YT and NT 12810-170 Street NW Edmonton, AB T5V 0A6

## **MANITOBA**

**Serving MB, Northwestern ON and NU** 1510 Wall Street NW

Winnipeg, MB R3G 2T3

## **ONTARIO**

## Serving ON and QC

1615 Clark Blvd Brampton, ON L6<u>T 4W1</u>

## **NEW BRUNSWICK**

**Serving the Atlantic Provinces** 

350 English Dr Moncton, NB E1E 3Y9



## 2019 Spring Edition

# **KLONDIKE** Lubricants Corporation

1-877-293-4691 • info@klondikelubricants.com • www.klondikelubricants.com

