Non-Detergent 30 Lubricating Oil



PRODUCT DESCRIPTION

Non-Detergent 30 Lubricating Oil is a mineral base oil product for use in systems where non detergent oils are specified.

APPLICATIONS

Non-Detergent 30 Lubricating Oil is recommended for use in air compressors and hydraulic systems where the use of non-detergent oils is specified. Non-detergent oils are also effective for the lubrication of bearings and chains in non-critical once-through systems and as a general purpose shop lubricant. Not for use in automotive gasoline engines.











TYPICAL TECHNICAL PROPERTIES

| PROPERTY | TEST METHOD | NON-DE- TERGENT 30 |
|-----------------------|-------------|--------------------------|
| SAE Viscosity Grade | | 30 |
| Viscosity cSt @ 40°C | ASTM D445 | 87.0 |
| Viscosity cSt @ 100°C | ASTM D445 | 10.9 |
| Viscosity index | ASTM D2270 | 110 |
| Color | | 1.0 |

All stated properties are typical of standard production and may vary. KLONDIKE reserves the right to change product specifications and/or performance properties at its discretion and without notice.

FEATURES AND BENEFITS

Non-Detergent 30 Lubricating Oil is formulated using 100% pure, virgin base oil. Non detergent chemistry ensures there is no material in the formula to create deposits on metal surfaces ensuring clean operation. Resistant to oxidation and withstands high heat for long service life.

Non-Detergent 30 Lubricating Oil provides value through the following benefits:

- Effective economical lubricant
- Good corrosion and wear protection

Non-Detergent 30 Lubricating Oil

PRODUCT NUMBERS

| NON-DETERGENT 30 LUBRICATING OIL | Jug: 4.73 L / 1.25 GAL | KL-105840 |
|-------------------------------------|------------------------|-----------|
| | Pail: 18.9 L / 5 GAL | KL-105880 |
| | Drum: 208 L / 55 GAL | KL-I05890 |
| | Tote: 1040 L / 275 GAL | KL-105895 |
| | Bulk | KL-105899 |

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other KLONDIKE product, please visit www.klondikelubricants.com or call 1-877-293-4691. When disposing of used product, be responsible to the environment.

BRAVING THE FORCE OF MOVEMENT

KLONDIKE stands for robust, reliable, high quality products tailored to suit the requirements of the on- and off-road heavy duty, automotive and industrial markets. Our solutions span from trend-setting retail lubricants through small-batch custom formulations to large bulk orders ready for immediate delivery.

The extensive KLONDIKE product range includes premium oils, lubricants, greases, chemicals and specialty fluids formulated with virgin base oils and protective inhibitors. Designed to handle the most extreme climates and operating conditions, the KLONDIKE products protect and extend the life of your equipment, optimize performance and improve productivity while meeting and exceeding industry standards and specifications.

KLONDIKE Lubricants Corporation

Toll-free 1-877-293-4691

info@klondikelubricants.com www.klondikelubricants.com