

KLONDIKE Tacky Saw Guide Oils



PRODUCT DESCRIPTION

KLONDIKE Tacky Saw Guide Oils are custom engineered formulations designed to exceed the requirements of high capacity saw blades and guides in mill applications.

APPLICATIONS

KLONDIKE Tacky Saw Guide Oils are recommended for all types of thin kerf saw blades on modern gang saws and edgers. The choice of viscosity grade depends on equipment type, lubricant delivery system design, and ambient temperatures.



TYPICAL TECHNICAL PROPERTIES

PROPERTY	TACKY SAW GUIDE OIL ISO 100	TACKY SAW GUIDE OIL ISO 150
ISO Viscosity Grade	100	150
Gravity, °API	28.0	27.0
Pour Point °C,	-30	-20
Flash Point, °C	210	220
Viscosity		
cSt at 40° C	100	150
cSt at 100° C	13.8	14.5
Viscosity Index (min)	95	95
Rust Test (ASTM D665)	PASS	PASS

All stated properties are typical of standard production and may vary. KLONDIKE reserves the right to change product specifications and/or performance properties at its discretion and without notice.

FEATURES AND BENEFITS

KLONDIKE Tacky Saw Guide Oils are formulated from premium base stocks selected for their oxidation stability and rust inhibition. Proprietary tackiness additives provide superior adhesion to the blade and guide surfaces to resist fling off and lubricant waste. Formulated to control pitch and resin build up on blade surfaces for outstanding cut quality and overall cutting efficiency.

KLONDIKE Tacky Saw Guide Oils deliver value through the following benefits:

- Effective friction reducing film for outstanding wear protection
- Excellent oxidation stability
- Control pitch and resin build up
- Superior corrosion resistance and protection of steel, copper, and bronze
- Superior adhesion ability for stray mist control and reduced lubricant fling



KLONDIKE Tacky Saw Guide Oils



HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other KLONDIKE product, please visit www.klondikelubricants.com or call 1-877-293-4691. When disposing of used product, be responsible to the environment.

PRODUCT NUMBERS

ISO 100 TACKY SAW GUIDE	Drum: 208 L / 55 GAL	KL-I08390
ISO 150 TACKY SAW GUIDE	Drum: 208 L / 55 GAL	KL-I08590

BRAVING THE FORCE OF MOVEMENT

KLONDIKE stands for robust, reliable, high quality products tailored to suit the requirements of the on- and off-road heavy duty, automotive and industrial markets. Our solutions span from trend-setting retail lubricants through small-batch custom formulations to large bulk orders ready for immediate delivery.

The extensive KLONDIKE product range includes premium oils, lubricants, greases, chemicals and specialty fluids formulated with virgin base oils and protective inhibitors. Designed to handle the most extreme climates and operating conditions, the KLONDIKE products protect and extend the life of your equipment, optimize performance and improve productivity while meeting and exceeding industry standards and specifications.

KLONDIKE Lubricants Corporation

Toll-free 1-877-293-4691

info@klondikelubricants.com
www.klondikelubricants.com

