

KLONDIKE ULV Full Synthetic Automatic Transmission Fluid



PRODUCT DESCRIPTION

KLONDIKE ULV Full Synthetic Automatic Transmission Fluid is a premium performance, full synthetic automatic transmission fluid formulated for specific automatic transmissions requiring ultra-low viscosity oil. This specially formulated combination of 100% synthetic base oils and state-of-the-art additive technology ensures ultimate performance and maximized fuel economy potential in modern automatic transmissions.

APPLICATIONS

KLONDIKE ULV Full Synthetic Automatic Transmission Fluid is an advanced automatic transmission fluid designed for use in automatic transmissions manufactured by North American, European, Asian, and other manufactures around the world using 9 and 10 speed high performance transmission designs.

Typical applications include:

- Passenger cars and light trucks requiring ULV ATF



FEATURES AND BENEFITS

KLONDIKE ULV Full Synthetic Automatic Transmission Fluid is formulated with full synthetic low viscosity base stocks and technologically advanced additives that provide oxidation and thermal stability, friction control, load-carrying ability, as well as corrosion and wear protection. Specialized additive chemistry offers anti-shudder durability, friction stability, shift quality, anti-wear protection, oxidation stability, and outstanding low and high temperature operation characteristics. Oxidation resistant additives minimize the formation of deposits, sludge, varnish, and foam and demonstrate outstanding fluid life and component durability. Advanced friction modifiers combined with a highly optimized low viscosity formulation have been proven to show improvements in fuel economy because of very low frictional energy loss in operation.

KLONDIKE Universal Full Synthetic ATF provides value through the following benefits:

- **Full synthetic** – premium synthetic base oils and advanced additive technology improves fuel economy and operating efficiency.
- **Advanced additive chemistry** – smooth, consistent shifting performance with positive lockup.
- **Anti-wear protection** – eliminates premature wear (especially at start-up) and maintains its properties at high temperatures under extreme loads or in severe operating conditions.
- **All climate application** – highly stable even at extreme high and low temperatures for year-round protection and performance.
- **Extended service life** – retains frictional performance properties and protects against oxidation, rust, and corrosion far beyond traditional fluids.
- **Compatibility** – ideal for top-up or complete replacement for OEM fluids.



KLONDIKE ULV Full Synthetic Automatic Transmission Fluid

SPECIFICATIONS AND APPROVALS

KLONDIKE ULV Full Synthetic Automatic Transmission Fluid meets the performance requirements of the following fluid applications:

- Ford Mercon® ULV – WSS-M2C949-A
- Mercedes Benz MB 236.17
- GM Dexron® ULV

Recommended for use in applications requiring Dexron ULV or Mercon ULV fluids such as

- Ford 10R60
- GM 10L80
- Ford 10R80
- GM 10L90

TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	UNIVERSAL FULL SYN ATF
Specific Gravity	ASTM D4052	0.835
Viscosity @ 40°C cSt	ASTM D445	17.1
Viscosity @ 100°C cSt	ASTM D445	4.25
Viscosity Index	ASTM D2270	163
Pour Point °C	ASTM D5950	-54°C
Flash Point °C	ASTM D92	220
Brookfield Viscosity @ -40°C, cP	ASTM D2983	4,750

All stated physical properties are typical of standard production and may vary.

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other KLONDIKE product, please visit www.klondikelubricants.com or call 1-877-293-4691. When disposing of used product, be responsible to the environment.

PRODUCT NUMBERS

ULV FULL SYNTHETIC ATF	Bottle: 1 L	KL-TF2640
	EZE-KEG: 52 L / 13.74 GAL	KL-TF2684
	Drum: 208 L / 55 GAL	KL-TF2690

BRAVING THE FORCE OF MOVEMENT

KLONDIKE stands for robust, reliable, high quality products tailored to suit the requirements of the on- and off-road heavy duty, automotive and industrial markets. Our solutions span from trend-setting retail lubricants through small-batch custom formulations to large bulk orders ready for immediate delivery.

The extensive KLONDIKE product range includes premium oils, lubricants, greases, chemicals and specialty fluids formulated with virgin base oils and protective inhibitors. Designed to handle the most extreme climates and operating conditions, the KLONDIKE products protect and extend the life of your equipment, optimize performance and improve productivity while meeting and exceeding industry standards and specifications.

KLONDIKE Lubricants Corporation

Toll-free 1-877-293-4691

info@klondikelubricants.com
www.klondikelubricants.com

