KLONDIKE Drill Rod Grease

PRODUCT DESCRIPTION

KLONDIKE Drill Rod Grease is a long fibred, tacky, tenacious grease specially formulated and designed for the lubrication of drill rods.

APPLICATIONS

KLONDIKE Drill Rod Grease is designed to lubricate and protect long sections of drill rod and pipe operating in extreme conditions underground. Tacky and tenacious formulation stays where it is put and resists wipe off and wash off for reduced friction between the drill rod and the underground strata as well as improved drill efficiency.



FEATURES AND BENEFITS

KLONDIKE Drill Rod Grease utilizes an optimized barium complex thickened formulation, designed for enhanced performance in extreme drilling conditions over a wide temperature range. Drill Rod Grease has a long fibred, tacky texture and enhanced mechanical stability for long service life once applied.

KLONDIKE Drill Rod Grease uses a thickener structure that inherently resists emulsification and water washout in service. Good low temperature capabilities allow the lubricant film to maintain its adhesive characteristics and durable protection under demanding conditions.

KLONDIKE Drill Rod Grease delivers value through the following benefits:

- Tacky adhesive formula resists throw off the rod and seals out contamination from critical areas helping to extend equipment life.
- **High Water Resistance** ideal for applications and components exposed to moisture.
- Wide temperature range resists lubricant loss or excessive hardening when exposed to high temperatures.
- **Mechanically stable** cohesive structure for enhanced performance and ease of application.

KLONDIKE Drill Rod Grease

TYPICAL TECHNICAL PROPERTIES

PROPERTY	DRILL ROD	
NLGI Grade	3	
Appearance	Fibrous and tacky	
Thickener Type	Barium Com- plex	
Base Oil	Mineral	
Base oil Viscosity @ 40°C (cSt)	150	
Worked penetration (x60) @25°C	240	
Dropping point, °C	200	
Rust prevention	Pass	
Water washout (max)	5.0%	

All stated physical properties are typical of standard production and may vary.

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other KLONDIKE product, please visit www.klondikelubricants.com or call 1-877-293-4691. When disposing of used product, be responsible to the environment.

PRODUCT NUMBERS		
DRILL ROD GREASE	Pail: 15.9 KG / 35 LB	KL-GR9880

BRAVING THE FORCE OF MOVEMENT

KLONDIKE stands for robust, reliable, high quality products tailored to suit the requirements of the on- and off-road heavy duty, automotive and industrial markets. Our solutions span from trend-setting retail lubricants through small-batch custom formulations to large bulk orders ready for immediate delivery.

The extensive KLONDIKE product range includes premium oils, lubricants, greases, chemicals and specialty fluids formulated with virgin base oils and protective inhibitors. Designed to handle the most extreme climates and operating conditions, the KLONDIKE products protect and extend the life of your equipment, optimize performance and improve productivity while meeting and exceeding industry standards and specifications.

KLONDIKE Lubricants Corporation

Toll-free 1-877-293-4691

info@klondikelubricants.com www.klondikelubricants.com