

KLONDIKE Fifth Wheel Grease



PRODUCT DESCRIPTION

KLONDIKE Fifth Wheel Grease is a tacky, tenacious grease specially formulated and designed for the lubrication of tractor Fifth wheel plates.

APPLICATIONS

KLONDIKE Fifth Wheel Grease is designed to handle the severe load conditions of trailers sliding on and off Fifth wheel plates. Contains molybdenum for enhanced lubrication and protection against wear associated sliding action. Tacky, tenacious formulation stays where it is put and resists wipe off and wash off even when exposed to water or snow.

FEATURES AND BENEFITS

KLONDIKE Fifth Wheel Grease utilizes an optimized barium complex thickened formulation, designed for enhanced performance over a wide temperature range. Long fibred, tacky texture and enhanced mechanical stability for long service life once applied.

KLONDIKE Fifth Wheel Grease uses a thickener structure that inherently resists emulsification and water washout in service. Good low temperature capabilities with the enhanced characteristics of molybdenum allow the lubricant film to maintain its adhesive characteristics and durable protection under demanding conditions.

KLONDIKE Fifth Wheel Grease delivers value through the following benefits:

- **Tacky adhesive formula** – resists removal from wear surface helping to extend equipment life.
- **High Water Resistance** – ideal for applications and components exposed to moisture.
- **Wide temperature range** – resists lubricant loss or excessive hardening when exposed to high temperatures.
- **Mechanically stable** – cohesive structure for enhanced performance and ease of application.



KLONDIKE Fifth Wheel Grease

TYPICAL TECHNICAL PROPERTIES

PROPERTY	Fifth Wheel Grease
NLGI Grade	2
Appearance	Fibrous and tacky
Colour	Black
Thickener Type	Barium Com-plex
Base Oil	Mineral
Base oil Viscosity @ 40°C (cSt)	100
Worked penetration (x60) @25°C	275
Dropping point min, °C	165
Rust prevention	Pass
Load wear index	65
Rust prevention	Pass

All stated physical properties are typical of standard production and may vary.

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other KLONDIKE product, please visit www.klondikelubricants.com or call 1-877-293-4691. When disposing of used product, be responsible to the environment.

PRODUCT NUMBERS

FIFTH WHEEL GREASE	Pail: 15.9 KG / 35 LB	KL-GR8080
--------------------	-----------------------	-----------

BRAVING THE FORCE OF MOVEMENT

KLONDIKE stands for robust, reliable, high quality products tailored to suit the requirements of the on- and off-road heavy duty, automotive and industrial markets. Our solutions span from trend-setting retail lubricants through small-batch custom formulations to large bulk orders ready for immediate delivery.

The extensive KLONDIKE product range includes premium oils, lubricants, greases, chemicals and specialty fluids formulated with virgin base oils and protective inhibitors. Designed to handle the most extreme climates and operating conditions, the KLONDIKE products protect and extend the life of your equipment, optimize performance and improve productivity while meeting and exceeding industry standards and specifications.

KLONDIKE Lubricants Corporation

Toll-free 1-877-293-4691

info@klondikelubricants.com
www.klondikelubricants.com

