

Safety Data Sheet

Date of the latest revision of the safety data sheet: 11-20-2019

Supercedes: 11-20-2019

KLONDIKE ISO 320 EP Full Synthetic Industrial Gear Lubricant

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name KLONDIKE ISO 320 EP Full Synthetic Industrial Gear Lubricant

Other means of identification

Product Code(s) Synonyms

Recommended use of the chemical and restrictions on use

Recommended Use Lubricant.

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

KLONDIKE Lubricants Corporation 3078 275th Street Langley,

BC, V4W 3L4 Canada

General information 1-877-293-4691

info@klondikelubricants.com

Emergency Contact:

Chemtrec (Within US) 1-800-424-9300 Chemtrec

(International) 1-703-527-3887

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization Category 1

Label elements

EMERGENCY OVERVIEW

WARNING

Hazard statements

May cause an allergic skin reaction



Appearance Amber colored liquid

Physical state Viscous Liquid

Odor Mild petroleum odor Mild sulfur odor

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Material name: KLONDIKE ISO 320 EP Full Synthetic Industrial Gear Lubricant

SDS CAD

Wear protective gloves

Precautionary Statements - Response

IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other information

3. COMPOSITION/INFORMATION ON INGREDIENTS

Petroleum based lubricating fluid. **Common Name Chemical Family** Petroleum hydrocarbon mixture.

Chemical name	CAS-No	Weight %	Trade secret
1-Decene, homopolymer, hydrogenated	68037-01-4	0-70	*
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	0-75	*
Long-chain alkyl amine	Proprietary	0.07-0.15	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures

General advice No hazards which require special first aid measures.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if Eve contact

present and easy to do. Continue rinsing. If irritation persists, call a physician.

Skin contact Wash skin with soap and water. If symptoms persist, call a physician.

Inhalation If symptoms persist, call a physician. Move victim to fresh air.

Do NOT induce vomiting. If symptoms persist, call a physician. Ingestion

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO₂). Dry chemical. Foam. Water can be used to keep surrounding materials cool.

Large Fires Contact emergency personnel.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Combustible material.

Material name: KLONDIKE ISO 320 EP Full Synthetic Industrial Gear Lubricant

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO 2).

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal protection Wear protective gloves/clothing and eye/face protection.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Absorb with earth, sand or other non-combustible material and transfer to containers for

later disposal.

Methods for cleaning upSoak up with inert absorbent material. Prevent product from entering drains.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Keep away from open flames, hot surfaces and sources of ignition. Avoid contact with skin

and eyes.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from open flames, hot surfaces and sources of ignition. Keep containers tightly

closed in a dry, cool and well-ventilated place. Keep out of the reach of children.

Incompatible Products Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum distillates, hydrotreated	TWA: 5 mg/m ³	TWA: 5 mg/m ³	IDLH: 2500 mg/m ³
heavy paraffinic	_		TWA: 5 mg/m ³
64742-54-7			STEL: 10 mg/m ³

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face Protection Goggles. Safety glasses.

Skin and body protection Long sleeved clothing. Protective gloves.

Respiratory protection In case of inadequate ventilation wear respiratory protection.

General Hygiene Considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and

immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Viscous Liquid Appearance Amber colored liquid

Appearance Amber colored liquid Odor Mild petroleum odor
Mild sulfur odor

Color amber Odor threshold No information available

(based on components)

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

PH No information available

Melting point/freezing point No information available

Boiling Point/Range No information available

Flash point > 148.9 °C / > 300 °F

No information available

Evaporation rate No information available Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available
No information available

Specific gravity 0.84-0.90

Water solubilityNo information availableSolubility in other solventsNo information availablePartition coefficientNo information available

Autoignition temperature

Decomposition temperatureNo information availableKinematic viscosity62-730 @40C mm2/sDynamic viscosityNo information availableExplosive propertiesNo information availableOxidizing propertiesNo information available

Other information

Softening point
VOC Content
Density
Bulk density
No information available
No information available
No information available
No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under normal conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous polymerization Hazardous polymerization does not occur.

Material name: KLONDIKE ISO 320 EP Full Synthetic Industrial Gear Lubricant

Version #: 01 Issue date: 20-11-2019 4

Conditions to avoid

Excessive heat.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information No data available

Inhalation Inhalation of vapors in high concentration may cause irritation of respiratory system.

Eye contact Avoid contact with eyes. May cause irritation.

Skin contact May cause sensitization by skin contact.

Ingestion Do NOT taste or swallow.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum distillates, hydrotreated	> 15 g/kg (Rat)> 24 g/kg (Rat)	> 5000 mg/kg (Rabbit)	= 2062 ppm (Rat)4 h
heavy paraffinic 64742-54-7			
Long-chain alkyl amine	612 mg/kg (Rat)	251 mg/kg (Rat)	157 ppm (Rat) 4h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.CarcinogenicityNo information available.

Chemical name	ACGIH	IARC	NTP	OSHA
Petroleum distillates,	-	Group 1	Known	X
hydrotreated heavy		i -		
paraffinic				
64742-54-7				

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration hazard
No information available.
No information available.
No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Crustacea
Petroleum distillates, hydrotreated heavy	-	5000: 96 h Oncorhynchus mykiss	1000: 48 h Daphnia magna mg/L

paraffinic	mg/L LC50	EC50
64742-54-7		

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste Disposal Method Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

14. TRANSPORT INFORMATION

DOT Not regulated

15. REGULATORY INFORMATION

International Inventories

Does not comply **TSCA DSL/NDSL** Does not comply Does not comply **EINECS/ELINCS** Does not comply **ENCS IECSC** Does not comply **KECL** Does not comply **PICCS** Does not comply **AICS** Does not comply

Legend:

All components in this product are listed on the US Toxic Substances Control Act (TSCA) inventory of chemicals.

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any

Material name: KLONDIKE ISO 320 EP Full Synthetic Industrial Gear Lubricant

chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Petroleum distillates, hydrotreated	X	-	X
heavy paraffinic			
64742-54-7			

U.S. EPA Label Information

EPA Pesticide registration number Not Applicable

16. OTHER INFORMATION

NFPA Instability 0 Health hazards 1 Flammability 1 **Physical and Chemical** Hazards -HMIS Health hazards 1 Flammability 1 Physical hazards 0 Personal protection X

Issuing Date 02-Feb-2010 **Revision Date** 20-Nov-2019 **Revision Note**

SDS sections updated 1 2 3 4 5 6 7 8 9 10 11 14 16

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Material name: KLONDIKE ISO 320 EP Full Synthetic Industrial Gear Lubricant