

KLONDIKE Power Steering Fluid



PRODUCT DESCRIPTION

KLONDIKE Power Steering Fluid is specially formulated for many foreign and domestic vehicles.

APPLICATIONS

KLONDIKE Power Steering Fluid is used in many power steering systems in automobiles, trucks, and heavy equipment using a fluid of this type.

Check your owner's manual for specified or recommended fluid type.



SPECIFICATIONS AND APPROVALS

KLONDIKE Power Steering Fluid meets and exceeds the requirements of the following:

- Chrysler MS-5931F (P/N 04883077)
- Ford M2C128-C/D, M2C195-A
- Ford Mercon, ESP-M2C166-H
- GM 9985010 (Saginaw)
- GM Dexron III, II, Dexron
- MB 236.1
- Allison V-730D, C-4, C-3, C-2

FEATURES AND BENEFITS

KLONDIKE Power Steering Fluid is a premium formulation utilizing high quality base stocks with select additive technology to ensure performance and protection of power steering systems in many foreign and domestic vehicles.

KLONDIKE Power Steering Fluid contains appropriate chemistry to protect power steering systems against wear, will resist foaming, oxidation and corrosion, and will limit seal swell. This fluid will reduce operational noises including squeal because of enhanced properties in the fluid.

KLONDIKE Power Steering Fluid provides value through the following benefits:

- **Extended life** — reduced friction for excellent protection against wear
- **High viscosity index** – highly resistant to viscosity and thermal breakdown from extended high temperature operation
- **Wide application** – modern additive technology protects system components



KLONDIKE Power Steering Fluid

TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	POWER STEERING FLUID
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.86
Viscosity @ 40°C cSt	ASTM D445	34.2
Viscosity @ 100°C cSt	ASTM D445	7.0
Viscosity Index	ASTM D2270	170
Pour Point °C (°F)	ASTM D5950	-51°C (-60°F)
Color	ASTM D1500	1.5
Brookfield Vis @ -40°C	ASTM D2983	14,000
Copper Strip Corrosion (3 hours @ 100°C)	ASTM D130	1B
Rust Protection	ASTM D655A	PASS
Hydrolytic Stability Test	ASTM D2619	PASS
Foam Test	ASTM D892	<100/0 mL

All stated physical properties are typical of standard production and may vary.

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other KLONDIKE product, please visit www.klondikelubricants.com or call 1-877-293-4691. When disposing of used product, be responsible to the environment.

PRODUCT NUMBERS

KLONDIKE Power Steering Fluid	Bottle: 473 mL	KL-CH2032
	Bottle: 946 mL	KL-CH2040

BRAVING THE FORCE OF MOVEMENT

KLONDIKE stands for robust, reliable, high quality products tailored to suit the requirements of the on- and off-road heavy duty, automotive and industrial markets. Our solutions span from trend-setting retail lubricants through small-batch custom formulations to large bulk orders ready for immediate delivery.

The extensive KLONDIKE product range includes premium oils, lubricants, greases, chemicals and specialty fluids formulated with virgin base oils and protective inhibitors. Designed to handle the most extreme climates and operating conditions, the KLONDIKE products protect and extend the life of your equipment, optimize performance and improve productivity while meeting and exceeding industry standards and specifications.

KLONDIKE Lubricants Corporation

Toll-free 1-877-293-4691

info@klondikelubricants.com

www.klondikelubricants.com

