

KLONDIKE SAE 15W-40 CK-4 Full Synthetic Heavy Duty Engine Oil



PRODUCT DESCRIPTION

KLONDIKE SAE 15W-40 CK-4 Full Synthetic Heavy Duty Engine Oil is a high performance, mixed fleet engine oil recommended for naturally aspirated and turbocharged diesel and gasoline engines in which SAE 15W-40 viscosity grade and API CK-4 or SN service categories are specified.

APPLICATIONS

KLONDIKE SAE 15W-40 CK-4 Full Synthetic Heavy Duty Engine Oil is specifically engineered for engines operating under severe service in a wide range of climatic conditions and ambient temperatures. An ideal mixed fleet engine oil designed for naturally aspirated and turbocharged heavy duty diesel engines in mobile and stationary equipment where the API CK-4 service category and SAE 15W-40 viscosity grade are specified. Advanced API CK-4 additive technology is fully backwards compatible with, and replaces, service categories CJ-4, CI-4 Plus, and previous.

KLONDIKE SAE 15W-40 CK-4 Full Synthetic Heavy Duty Engine Oil also meets the requirements of Allison® C-4 for use in transmissions requiring a fluid of this type.

Some typical applications include:

- Current on-highway low emission diesel engines running on ultra-low sulfur diesel fuel.
- Current off-highway engines including those adapted for future emissions standards in construction, agriculture, marine, and mining applications.
- Heavy duty transmissions requiring fluid meeting Allison® C-4 specification.
- Mixed fleets where product consolidation is desired for performance and economics



FEATURES AND BENEFITS

KLONDIKE SAE 15W-40 CK-4 is a premium full synthetic heavy duty engine oil engineered to deliver outstanding wear protection and performance in modern heavy duty diesel engines. Formulated with premium, ultra-pure, full synthetic base oils and carefully balanced additive technology, this advanced engine oil delivers outstanding long-term performance for on- and off-highway heavy duty engine applications operating under high-load, high-stress conditions in all climates.

KLONDIKE SAE 15W-40 CK-4 Full Synthetic Heavy Duty Engine Oil contains field proven additive technology which delivers maximum control on engine wear, outstanding engine cleanliness, and high TBN and viscosity retention for outstanding lubricant life and maximum engine durability. Metal anti-wear protection exceeds API CK-4 standards and tough OEM specifications.

KLONDIKE SAE 15W-40 CK-4 Full Synthetic Heavy Duty Engine Oil is designed specifically to meet the stringent requirements of API Service Category CK-4 for heavy duty diesel engines running on Ultra Low Sulfur Diesel (ULSD) and equipped with advanced after treatment devices. Exceeds all soot control and particulate requirements of current emission control systems such as Exhaust Gas Recirculation (EGR), Diesel Particulate Filter (DPF), or Selective Catalytic Reduction (SCR).

KLONDIKE SAE 15W-40 CK-4 Full Synthetic Heavy Duty Engine Oil delivers value through the following benefits:

- **Premium full synthetic base oil** – excellent all-season performance characteristics.
- **Engine efficiency** – advanced additive technology keeps internal engine components clean, reduces oil consumption for long service life.
- **Outstanding anti-wear** – wear protection exceeds API CK-4 and tough OEM specifications even in severe service applications for maximum engine durability.
- **Emission compliant** – fully compliant with all current emission control equipment. Promotes extended DPF life helping to minimize maintenance costs.
- **Extended service life** – outstanding TBN and high viscosity retention supports extended lubricant life when used with regular oil testing.



KLONDIKE SAE 15W-40 CK-4 Full Synthetic Heavy Duty Engine Oil

SPECIFICATIONS AND APPROVALS

KLONDIKE SAE 15W-40 CK-4 meets the requirements of the following engine specifications:

- **ACEA** – European Service Categories E9, E7, E4, E2
 - **API Service Categories** – CK-4, CJ-4, CI-4 PLUS, CI-4 (and previous)
 - **API Service Categories** – SN, SM, SL (and previous)
 - **Caterpillar**® – ECF-3, ECF-2, ECF-1a
 - **Cummins**® – CES 20086, 20081, 20078, 20077, 20076
 - **Daimler** – MB 228.31, 228.3
 - **Detroit Diesel**® – 93K222, 93K218, 93K215, 93K214
 - **Deutz** – DQC III-IOLA
 - **FORD** – WSS-M2C171-F1, WSS-M2C171-E
 - **Global** – DHD-1
 - **JASO** – DH-2
 - **Mack**® – EOS-4.5, EO-O Premium Plus, EO-N Premium Plus, EO-M
 - **MAN** – 3275, 3575
 - **MTU** – Type 2.1, Type I, Type II
 - **Renault**® – VI RLD-4, RLD-3
 - **Volvo**® – VDS-4.5, VDS-4, VDS-3, VDS-2
 - **CID A-A-52306 / MIL-PRF-2104G**
- Other suitable uses include (but not limited to):**
- **Allison**® – C-4

Other applicable uses may exist. Please contact KLONDIKE for more information.

TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	SAE 15W-40 CK-4 FULL SYNTHETIC
Gravity; °API	ASTM D287	32.8
Specific Gravity @ 15.6°C	ASTM D4052	0.861
Viscosity @ 40°C (cSt)	ASTM D445	107.6
Viscosity @ 100°C (cSt)	ASTM D445	15.6
Viscosity Index	ASTM D2270	155
Flash Point °C	ASTM D92	225
Pour Point °C	ASTM D5950	-42
Cold Cranking Simulator @ -20°C, cP	ASTM D5293	5000
High temp/high shear Vis @ 150°C, cP	ASTM D5481	4.3
NOACK Volatility, % loss	ASTM D6375	10
Color	ASTM D1500	3.0
Zinc, wt %	ASTM D5185	0.127
Phosphorus, wt. %	ASTM D5185	0.115
Calcium wt. %	ASTM D5185	0.105
Sulfur, wt %	ASTM D4951	0.32
Magnesium, wt %	ASTM D5185	0.1
Molybdenum, wt %	ASTM D5185	0.0066
Sulfated Ash, wt %	ASTM D874	0.99
Nitrogen, wt %	ASTM D4629	0.105
Pumping Viscosity @ (-25°C),cP	ASTM D4684	19,000
TAN, mgKOH/g	ASTM D664	2.9
TBN, mgKOH/g	ASTM D2896	10

All stated physical properties are typical of standard production and may vary.



KLONDIKE SAE 15W-40 CK-4 Full Synthetic Heavy Duty Engine Oil

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other KLONDIKE product, please visit www.klondikelubricants.com or call 1-877-293-4691. When disposing of used product, be responsible to the environment.

DISCLAIMER

Always follow OEM recommendations for fluid viscosity and API service category. KLONDIKE takes no responsibility for product misuse or misapplication.

PRODUCT NUMBERS

15W-40 CK-4 FULL SYNTHETIC	Jug: 4.73 L / 1.25 GAL	KL-HD3560
	Pail: 18.9 L / 5 GAL	KL-HD3580
	Drum: 208 L / 55 GAL	KL-HD3590
	Tote: 1040 L / 275 GAL	KL-HD3595
	Bulk	KL-HD3599

BRAVING THE FORCE OF MOVEMENT

KLONDIKE stands for robust, reliable, high quality products tailored to suit the requirements of the on- and off-road heavy duty, automotive and industrial markets. Our solutions span from trend-setting retail lubricants through small-batch custom formulations to large bulk orders ready for immediate delivery.

The extensive KLONDIKE product range includes premium oils, lubricants, greases, chemicals and specialty fluids formulated with virgin base oils and protective inhibitors. Designed to handle the most extreme climates and operating conditions, the KLONDIKE products protect and extend the life of your equipment, optimize performance and improve productivity while meeting and exceeding industry standards and specifications.

KLONDIKE Lubricants Corporation

Toll-free 1-877-293-4691

info@klondikelubricants.com
www.klondikelubricants.com

